Technical Sheet

TW
Anchor for Suspended Ceiling

The TW is a Ø6.0 mm wedge anchor for suspended ceilings.







Features

Material

- Steel
- White zinc plated

Benefits

- Suitable for the installation of suspended ceilings or elements

Applications

Application

- False ceilings

Suitable for


- Non-cracked concrete
- Solid brick
- Solid stone

Technical Sheet

TW
Anchor for Suspended Ceiling

Technical Data







Product Dimensions


Reference	Metallic fixings dimensions							Installation data		
	Other					Product Reference	Product Dimensions[mm]	Installation data		Spacing and edge distances
	Hole diameter [d_o] x depth [h_1] in substrate[mm]	Min. setting depth [h_{ef}] [mm]	Qty per box[stk]	Qty per outer box	Weight[kg]		Internal eye[mm]	Min. hole depth [h_1][mm]	Nominal embedment depth [h_{nom}] [mm]	Min. support thickness[mm]
TW6.0x60	Ø6x60	35	100.0	1600	0.011	TW	6	>=50	45	100


TW
Anchor for Suspended Ceiling

Installation









Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®