

Technical Sheet

**FRÜL
SIDER**

SIMPSON
StrongTie

TW Anchor for Suspended Ceiling

The TW is a Ø6.0 mm wedge anchor for suspended ceilings.

Features

Material

- Steel
- White zinc plated

Benefits

- Suitable for the installation of suspended ceilings or elements

Applications

Application

- False ceilings

Suitable for

- Non-cracked concrete
- Solid brick
- Solid stone

NEW

EZ




Technical Sheet

**FRIUL
SIDER**

**SIMPSON
StrongTie**

TW
Anchor for Suspended Ceiling

Technical Data



Product Dimensions

Reference	Metallic fixings dimensions						Installation data			
	Other					Product Reference	Product Dimensions[mm]	Installation data		Spacing and edge distances
	Hole diameter [d _o] x depth [h ₁] in substrate[mm]	Min. setting depth [h _{ef}] [mm]	Qty per box[stk]	Qty per outer box	Weight[kg]		Internal eye[mm]	Min. hole depth [h ₁][mm]	Nominal embedment depth [h _{nom}] [mm]	Min. support thickness[mm]
TW6.0x60	Ø6x60	35	100.0	1600	0.011	TW	6	>=50	45	100

TW Anchor for Suspended Ceiling

Installation

