Technical Sheet

CCQ
Column Cap for use with SSH Screws

The CCQ type Column Caps can be made to order for all standard timber or engineered timber sizes.CCQ Column Caps are suitable for most post to beam installations using SSH8.0X60 connector screws supplied with the caps. Specify the variable dimensions as shown in the Column Cap Made to Order Form below.



Features

Material

Hot dip galvanised mild steel

Advantages

Easily and quickly installed with SSH screws supplied so no drilling for bolt holes or sourcing different length bolts required.








Technical Sheet

CCQ
Column Cap for use with SSH Screws

Technical Data



Product Dimensions

Reference	Connector Dimensions											
	Product Dimensions[mm]										Holes	
	B[mm]	t1[mm]	t2[mm]	A, A2, A3		C, C1, C2		H (2)			Legs	Body
				Min[mm]	Max[mm]	Min[mm]	Max[mm]	Min[mm]	Max[mm]		Ø9	Ø9
SPEC E ECCLRQ	300	5	5	75	250	140	190	75	250		8	16

1. Refer to individual dimensioned drawings (in product gallery) or order form for relevant dimension.
2. All referenced column cap dimensions are internal

Installation

Installation

Use SSH8.0x60 (75136) screws supplied wih the column caps.
Install SSH screws with a 13mm Hex Head Socket or T40 Torq Drive bit..
It is recommended that the SSH screws are installed with torque dril driver, not an impact driver.

Ordering

Use CCQ Column Cap Made to Order Form below.
All referenced column cap width dimensions are internal.








Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®