

ETB

Concealed Beam Hanger

The ETB concealed connector comes in two parts. The first is fixed to the header timber with nails provided, while the second part is fitted to the end of the beam with screws. No slots or dowel holes are necessary, speeding up installation.
Note: fixings are included

Features

Material

- Joist plate: 10mm aluminium.
- Header plate: 6mm aluminium.

Benefits

- Concealed connection.
- Multiple applications.

Applications

Header member

Glulam joist and headers.

For Use With


Wood to wood connections only.




ETB Concealed Beam Hanger

Technical Data

Product Dimensions




Reference	Connector Dimensions												
	Other		Joist Size[mm]			Product Dimensions[mm]						Header holes[mm]	Joist Holes[mm]
	Qty per Box	Weight[kg]	Width	Height[mm]		A[mm]	B[mm]	C[mm]	D[mm]	t1[mm]	t2[mm]	Round	Round
			Min[mm]	Min[mm]	Max. [mm]							Ø5	Ø5.4
ETB90-B	25.0	0.1	70	115	150	90	60	58	69	6	10	6	4
ETB120-B	25.0	0.14	70	150	200	121	60	85	95	6	10	9	6
ETB190-B	25.0	0.27	90	220	300	195	75	138	165	6	10	19	11
ETB230-B	25.0	0.34	90	255	350	230	75	138	200	6	10	19	14



Wood/wood fastening- Characteristic values in kn

Reference	Hanger capacity			
	Wood/wood fastening- Characteristic values in kn			
	Number of Fasteners		Characteristic Capacities - Timber C24[kN]	
	Header		Joist	R _{1,k}
	Qty	Type	Qty	CSFT5,0x70
ETB90-B	6.0	CNA4,0x40	4	11.1
ETB120-B	9.0	CNA4,0x40	6	16.7
ETB190-B	19.0	CNA4,0x40	11	29.7
ETB230-B	19.0	CNA4,0x40	14	35.2



Product characteristic capacities - Timber beam to timber post

Reference	Hanger capacity			
	Product Characteristic Capacities - Timber Beam to Timber Post			
	Number of Fasteners		Product characteristic capacities - Timber C24[kN]	
	Header		Joist	R _{1,k}
	Qty	Type	Qty	CSFT5,0x70
ETB90-B	6.0	CNA4,0x40	4	11.1
ETB120-B	9.0	CNA4,0x40	6	16.7
ETB190-B	12.0	CNA4,0x40	9	22.2
ETB230-B	12.0	CNA4,0x40	10	22.2

ETB Concealed Beam Hanger

Installation

Fasteners


To achieve stated loads, nails and screws used must comply with the ETA-04/0013.

Installation


Installation of ETB is simplified by the use of a jig.

The pocket installation can be routed by using a Ø16 mm cutter with Ø30 mm washer.


CAUTION: ETB bracket should not be used for an assembly with a negative slope




installed cross section.




Countersunk within the supported member.




Face fix installation.




Face fix installation.




Face fix installation.





Face fix installation.



Positive slope installation.



Skewed installation.



Bois porteur	Bois porté	Bois porté	Bois porté	Bois porté	Bois porté
150x100	150x100	150x100	150x100	150x100	150x100
150x150	150x150	150x150	150x150	150x150	150x150
150x200	150x200	150x200	150x200	150x200	150x200
150x250	150x250	150x250	150x250	150x250	150x250
150x300	150x300	150x300	150x300	150x300	150x300

Technical Sheet

ETB
Concealed Beam Hanger



Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-

ETB
**Concealed Beam
Hanger**



www.strongtie.co.uk

