Technical Sheet

CLR

Concrete screw for structural fixings

The ideal anchor for reduced spacing and edge distances, as it does not generate tension in the base material: the special cutting thread enables quick installation, the built-in washer with knurling provides a complete and effective blocking, and the three certified installation depths increase the versatility of use. The A4 bimetal stainless steel version is designed for use in aggressive environments, while the CLR6 is available in four variants to meet all the requirements of installation systems and light carpentry.



SIMPSON StrongTie FRIULSIDER
Supplied in dual-branded packaging

R 120

Technical Data

Product Dimension

Reference	Metallic fixings dimensions									
	Product Dimensions[mm]		Other							Title
	Dim[mm]	Wrench size - SW[mm]	Hole diameter [d_o][mm]	Fixing thickness (tfix) for extra reduced embedment depth	Fixing thickness (tfix) for reduced embedment depth (hef,r)	Fixture thickness [tfi_x] (1)[mm]	Qty per box[pcs]	Qty per outer box	Weight[kg]	
72005B1006000	10x60	13	8	15	10	-	100.0	600	0.033	CLR
72005B1007500	10x75	13	8	30	25	10	100.0	500	0.039	CLR
72005B1013000	10x130	13	8	85	80	65	50.0	300	0.064	CLR
72005B1015000	10x150	13	8	105	100	85	50.0	300	0.066	CLR
72005B1206000	12x60	15	10	10	-	-	50.0	300	0.053	CLR
72005B1207500	12x75	15	10	25	15	-	50.0	300	0.063	CLR
72005B1210000	12x100	15	10	50	40	25	50.0	200	0.08	CLR
72005B1213000	12x130	15	10	80	70	55	25.0	150	0.1	CLR
72005B1215000	12x150	15	10	100	90	75	25.0	150	0.12	CLR
72005B1407500	14x75	16	12	25	15	-	50.0	200	0.082	CLR
72005B1410000	14x100	16	12	50	40	5	50.0	150	0.1	CLR
72005B1413000	14x130	16	12	80	70	35	20.0	120	0.13	CLR
72005B1608000	16x80	18	14	20	10	-	20.0	160	0.13	CLR
72005B1610000	16x100	18	14	40	30	-	25.0	150	0.15	CLR
72005B1613000	16x130	18	14▲	70	60	15	20.0	120	0.2	CLR
72005B1615000	16x150	18	14▲	90	80	35	10.0	60	0.23	CLR

▲ *Quantity and delivery terms to be agreed*

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®