
# Technical Sheet

TTFA4
**Decking Screw - Stainless Steel A4**

The TTFA4 is marine grade A4 stainless steel. Suitable for outdoor use and use in severe weather conditions, the TTFA4 has a ribbed countersunk head to ensure a neat finish and type 17 point to prevent timber from splitting upon insertion. The TTFA4 will not cause any discoloration of timber around the screw and is suitable for many timbers including oak, cedar and larch. TTFA4 is CE marked to EN14592, has a 6 lobe drive with driver bits included in every box of screws.

**Find it in the Solid Wood Application >**














## Features

### Material

**Stainless steel - A4**

### Features

- CE marked to EN14592
- 6 lobe drive
- Ribbed flat countersunk head
- Coarse thread
- Type 17 point
- Marine grade stainless steel (A4)

## Applications


### Common Applications

- Timber to timber
- Extreme environments
- Decking to timber
- Precious woods including oak, cedar and larch

# Technical Sheet

TTFA4
**Decking Screw - Stainless Steel A4**

# Technical Data




## Product Dimensions


| Reference | Fasteners Dimensions | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | Item Code | Other | | Product Dimensions[mm] | | | | |
| | | Packaging | Weight[kg] | d[mm] | l[mm] | $d_h$[mm] | lg[mm] | Driver Bit[mm] |
| TTFA44.2X35T-20 | 74385 | 250 | 0.002 | 4.2 | 35 | 7 | 20 | T-20 |
| TTFA44.2X45T-20 | 74386 | 250 | 0.003 | 4.2 | 45 | 7 | 23 | T-20 |
| TTFA44.2X55T-20 | 74387 | 250 | 0.003 | 4.2 | 55 | 7 | 27.5 | T-20 |
| TTFA44.8X75T-20 | 74389 | 100 | 0.006 | 4.8 | 75 | 7 | 35 | T-20 |

## Collated screws





| Reference | Fasteners Dimensions | | | | | | |
|---|---|---|---|---|---|---|---|
| | Item Code | Other | Product Dimensions[mm] | | | | |
| | | Packaging | d[mm] | l[mm] | $d_h$[mm] | lg[mm] | Driver Bit[mm] |



## Characteristic Capacities

| Reference | Screw Parameters | | | |
|---|---|---|---|---|
| | Characteristic parameters | | | |
| | Characteristic Yield Moment – My,k[Nm] | Characteristic withdrawal parameter - $f_{ax,k,90°}$[N/mm²] | Characteristic head pull-through parameter - $f_{head,k}$[N/mm²] | Characteristic tensile capacity - $f_{tens,k}$[kN] |
| TTFA44.2X35T-20 | 2575 | 17 | 20.4 | 4.2 |
| TTFA44.2X45T-20 | 2575 | 17 | 20.4 | 4.2 |
| TTFA44.2X55T-20 | 2575 | 17 | 20.4 | 4.2 |
| TTFA44.8X75T-20 | 4371 | 20.7 | 16.4 | 5.6 |

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®