
Technical Sheet

FBCS
Fibre Cement Screw

FBCS screws are used in humid conditions both indoor and outdoor thanks to the impressive Impreg®+ coating. They are particularly suited for fixing fibre cement boards to timber. They are also suitable for timber to timber applications. The sharp point means that the screws can also be used to fix to light gauge steel up to 1mm thick. The ribbed countersunk flat head countersinks flush into the cement board/timber leaving a neat finish. FBCS screws are CE marked to EN14566 and have a PH2 drive recess.
Available as loose screws or flat belt collated for standard autofeed screwdrivers.





Features

Material

Steel - Impreg®+ coating

Features

- CE marked to EN14566
- PH drive
- Twin thread
- Ribbed countersunk head
- Sharp point
- Impreg®+ coating

Applications

Common Applications


- Fibre cement board to timber
- timber to timber
- Can also be used to fix to steel up to 1mm thick

Technical Sheet

FBCS
Fibre Cement Screw

Technical Data

Product Dimensions



Reference	Fasteners Dimensions							
	Item Code	Other		Product Dimensions[mm]				
		Box Quantity	Weight[kg]	d[mm]	l[mm]	dh[mm]	lg[mm]	Driver Bit[mm]
FBCS3.9X25	75453	250.0	0.001	3.9	25	6.8	18	PH2
FBCS3.9X35	75454	250.0	0.002	3.9	35	6.8	28	PH2

FBCS Collated Screws

Reference	Fasteners Dimensions						
	Item Code	Other	Product Dimensions[mm]				
		Box Quantity	d[mm]	l[mm]	dh[mm]	lg[mm]	Driver Bit[mm]
FBCS3.9X25 Collated	75719	1000.0	3.9	25	6.8	18	PH2
FBCS3.9X35 Collated	75720	1000.0	3.9	35	6.8	28	PH2

* Flat tape collated for standard auto-feed screwdrivers
Also available Quik Drive collated

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®