Technical Sheet

FT
Frame Tie

When fixing windows, door frames etc. to masonry, the frame tie provides enhanced mortar keying and reduces the risk of injury from sharp edges.
Note: Frame tie should be fully embedded into mortar.
Note: NOT suitable for cavity wall construction





Technical Data

Product Dimensions

Reference	Connector Dimensions							
	Other		Product Dimensions[mm]				Holes Flange C	
	Material	Weight[kg]	A[mm]	B[mm]	C[mm]	t[mm]	Round	
							Ø4.1	Ø6
FT150	Galvanised	0.028	21.5	100	50	1	2	1
FT175	Galvanised	0.001	21.5	125	50	1	2	1
FT200	Galvanised	0.041	21.5	150	50	1	2	1
FT225	Galvanised	0.002	21.5	175	50	1	2	1
FT250	Galvanised	0.08	21.5	200	50	1	2	1
FT150S	Stainless Steel	0.028	21.5	100	50	1	2	1
FT175S	Stainless Steel	0.001	21.5	125	50	1	2	1
FT200S	Stainless Steel	0.033	21.5	150	50	1	2	1
FT225S	Stainless Steel	0.002	21.5	175	50	1	2	1
FT250S	Stainless Steel	0.003	21.5	200	50	1	2	1

NOTE: not suitable for cavity wall construction

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®