Technical Sheet

BRDHG

Grooved Countersunk Nail - Hot Dip Galvanised

Nail with a countersunk head and grooved shank for use indoors for fitting moulding or fixing hardwood and semi-hardwood boards to a wood base.
Particularly suited for use where the head should be countersunk, so that the nail is concealed.







Features

Features

- Countersunk head.
- Grooved shank.
- Hot dip galvanised coating.

Applications

Suitable For

- Wood to wood.

BRDHG
Grooved Countersunk Nail - Hot Dip Galvanised

Technical Data



Dimensions and drill holes

Reference	Fasteners Dimensions							
	Item Code	Other				Product Dimensions[mm]		
		Tun / DB nr.	NOB nr.	Qty per blister	Weight[kg]	d[mm]	l[mm]	dh[mm]
BRDHG1.7X35	74207	1950535	53291980	-	0.001	1.7	35	2.7
BRDHG1.7X40	74208	1950536	53291995	-	0.001	1.7	40	2.7
BRDHG2.0X50	74209	1950537	53292006	-	0.002	2	50	3.2
BRDHG2.3X60	74210	1950538	53292014	-	0.003	2.3	60	3.7
BRDHG2.8X75	74211	1950539	53292025	-	0.004	2.8	75	4.5

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®