


TML

Nylon plug for aerated concrete

TML concrete anchors Ø10 - Ø 14 mm are specially designed for fastening in aerated concrete. The anchor is placed after pre-drilling, whereby the external thread cuts positively into the building material and ensures a secure hold. The add-on parts can then be mounted using wood screws or metric screws.



Applications

Material

- Nylon dowel (polyamide PA6)


Benefits

- High quality nylon plug
- Suitable for wood screws and metric screws

Applications

- Pictures, Lamps
- Cable and pipe clamps
- Wall cupboards, shelves
- Signs
- Letterboxes

Nylon plug for aerated concrete



Reference	Nylon fixings dimensions									Nylon fixings Installation data			
	Info product[mm]									Installation data			
	Product Reference	Min. screw diameter [d][mm]	Max. screw diameter [d][mm]	Metric screw diameter	Anchor length [Lu] [mm]	Wrench[SW]	Qty per box[stk]	Qty per outer box	Weight[kg]	Hole diameter x anchor length [døxL] [mm]	Min. hole depth [h ₁] [mm]	Nominal embedment depth [h _{nom}][mm]	Min. support thickness [h _{min}] [mm]
6260100605000	TML	5.5	6	M6	40	6	25.0	250.0	0.005	10x50	60	50	75
6260100806000	TML	7	8	M8	50	8	25.0	250.0	0.008	12x60	70	60	85
6260101007000	TML	9	10	M10	60	10	25.0	250.0	0.01	14x70	80	70	100

Screw Length: $L_v = L_u + t_{fix}$

TML Nylon plug for aerated concrete

Installation

Suitable for

- Aerated concrete

