

Technical Sheet

SIMPSON

Strong-Tie

SSWSCB

SSWSCB TILE ROOFING Screw, Coarse Thread

SSWSCB is a stainless steel screw with a bugle head, coarse thread and a type 17 point. It is ideally suited to fastening roof tiles to wood.

Features

Material

- Stainless steel A2

Benefits

- Bugle head
- Tapered point
- Corrosion resistant material

Applications

Header member


- Softwood (Cedar, Spruce, Larch, Pine, Fir, Tsuga...)

Applications

- Tile roofing



BIT2SE



SSWSCB

SSWSCB TILE ROOFING Screw, Coarse Thread

Technical Data



Dimensions and characteristics values

Reference	Fasteners Dimensions[mm]						
	Product Dimensions[mm]			QD information			Other
	Head diameter[mm]	Thread diameter[mm]	Length of the screw[mm]	Screws per band	Compatible devices	Max. rotational speed[tr/min]	Screws per case
SSWSCB64E	8.5	4.6	64	30.0	QDPR064 / QD76 / QDPR076S	2500	1500.0


Mechanical properties (EN14592)

Reference	Screw Parameters				
	Characteristic parameters				
	Characteristic moment of elasticity - $M_{y,k}$ [Nm]	Characteristic pullout parameter[N/mm ²]	Characteristic head traversal parameter[N/mm ²]	Characteristic pulling capacity[kN]	Characteristic resistance to torsion - $R_{tor,k}$ [Nm]
SSWSCB64E	2.6	14	16	4.7	4.2

SSWSCB

SSWSCB TILE ROOFING Screw, Coarse Thread

Options

*Single Thread**Selfdrilling pin*

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

SSWSCB

**SSWSCB TILE ROOFING Screw,
Coarse Thread**

2026-10-22

www.strongtie.co.uk**SIMPSON****Strong-Tie®**