
Technical Sheet

ETFSS
Timber Frame Hold Down Strap

ETFSS hold down strap provides restraint against uplift to timber frame structures keeping them firmly to the ground.

- *Quick and simple to install*
- *One size strap suits cavities from 50 to 100mm*
- *Meets NHBC Technical requirements*
- *Meets NSAI Technical requirements*





Features

Material

- Stainless steel

Applications


Installation

Use all specified fasteners. Verify that the header can take the required fasteners specified in the table.
Note: Use 3.35x50mm stainless steel annular ring shank nails.

Technical Sheet

ETFSS
Timber Frame Hold Down Strap

Technical Data



Product Dimensions

Reference	Connector Dimensions								
	Product Dimensions[mm]					Joist	Flange B		Other
	A[mm]	B[mm]	C[mm]	D[mm]	t[mm]	Obround Ø4x6 Pan	Triangular	Round Ø4.1	Weight[kg]
ETFSS	75	723	33	380	1.2	2	2	6	0.25
ETFSS06	75	533	33	380	1.2	2	-	4	0.191

Performance Values

Reference	Holdowns capacity
	Product Capacity
	Fastener Qty
ETFSS (50mm Cavity)	6.0
ETFSS (51-100mm Cavity)	8.0
ETFSS06 (50mm Cavity)	4.0
ETFSS06 (51-100mm Cavity)	4.0

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®