

Technical Sheet

SIMPSON

Strong-Tie

DTHQ

Trim Head Decking Screw

The DTHQ is a trim head screw with coarse thread suitable for timber to timber applications such as decking. It has a Type 17 point which eliminates the need for pre-drilling and reduces the installation torque. The trim head provides a neat finish when countersunk into the timber and the Quik Guard® coating allows the screw to be used in external environments.



Features

Material

Steel - Quik Guard® coating

Benefits

- Type 17 point for faster, straighter drilling and reduced insertion torque
- Counter sunk trim head for a neater finish
- Coarse thread
- Quik Guard coating prevents rust staining and prolongs life, even outdoors
- Driver bits included (BIT2SUE)

Applications

Common Applications

- Decking
- Timber to timber




BIT2SUE



BIT2SUE

DTHQ
Trim Head Decking Screw

Technical Data



Product Dimensions UK

Reference	Fasteners Dimensions								
	Product Dimensions[mm]				QD information			Other	
	d _h [mm]	d[mm]	l[mm]	lg[mm]	Qty per Strip	Recommended RPM[tr/min]	Quik Drive Attachment	Qty per Box	Weight[kg]
DTHQ51E	6.2	4.2	51	37	30.0	2500.0	QDPR051E / QDPR064E / QD76KE	2000.0	6.6
DTHQ64E	6.2	4.2	64	50	30.0	2500.0	QDPR064E / QD76KE / QDPR076SKE	1500.0	6.2
DTHQ76E	6.2	4.5	76	55	30.0	2500.0	QD76KE / QDPR076SKE	1000.0	6.2

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-

DTHQ
Trim Head Decking
Screw



www.strongtie.co.uk