Technical Sheet

DTHQ
Trim Head Decking Screw

The DTHQ is a trim head screw with coarse thread suitable for timber to timber applications such as decking. It has a Type 17 point which eliminates the need for pre-drilling and reduces the installation torque. The trim head provides a neat finish when countersunk into the timber and the Quik Guard® coating allows the screw to be used in external environments.







BIT2SUE

Features

Material

Steel - Quik Guard® coating

Benefits

- Type 17 point for faster, straighter drilling and reduced insertion torque
- Counter sunk trim head for a neater finish
- Coarse thread
- Quik Guard coating prevents rust staining and prolonges life, even outdoors
- Driver bits included (BIT2SUE)

Applications


Common Applications

- Decking
- Timber to timber

Technical Sheet

DTHQ
Trim Head Decking Screw

Technical Data



Product Dimensions UK

Reference	Fasteners Dimensions								
	Product Dimensions[mm]				QD information			Other	
	d_h[mm]	d[mm]	l[mm]	lg[mm]	Qty per Strip	Recommended RPM[tr/min]	Quik Drive Attachment	Qty per Box	Weight[kg]
DTHQ51E	6.2	4.2	51	37	30.0	2500.0	QDPRO51E / QDPRO64E / QD76KE	2000.0	6.6
DTHQ64E	6.2	4.2	64	50	30.0	2500.0	QDPRO64E / QD76KE / QDPRO76SKE	1500.0	6.2
DTHQ76E	6.2	4.5	76	55	30.0	2500.0	QD76KE / QDPRO76SKE	1000.0	6.2

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®