Technical Sheet

QDHSD60E


Truck Bed and Mezzanine Floor Quik Drive Attachment

The QDHSD60E is designed to be used in conjunction with FHSD screws and TBG screws from 45mm to 64mm long. Use with FHSD screws to drill through steel thicknesses 3-5 mm for applications such as mezzanine floor installations. Use with TBG screws to drill through steel thicknesses 4-6 mm for truck bed/trailer installations.









Features

Material

- Manufactured containing PTFE
- No lubrication required

Benefits

- Connects easily with screw gun adapter or extension
- Possible 360° rotation of attachment on adapter or extension
- Self-lubricating material for long life and smooth operation
- Self-locking depth adjustment for consistent countersinking of screws
- Available as attachment only or with extension pole

Available Kits

QDHSD60E: Includes Quik Drive attachment, mandrel, driver bits, quiver and small carry case
QDHSD60KE: Includes Quik Drive attachment, mandrel, driver bits, quiver, large carry case and extension pole

Applications

Common Applications

Timber to steel applications:

- Mezzanine floor installations
- Truck bed/trailer installations

Technical Sheet

QDHSD60E

Truck Bed and Mezzanine Floor Quik Drive Attachment

Technical Data

Areas of use

Reference
QDHSD60KE
QDHSD60E

QDHSD60E
Truck Bed and Mezzanine Floor Quik Drive Attachment

Installation



Remove screw driver sleeve.



Then remove the cap.



Install the adaptor.



Insert the mandrel.



Engage the gun with the mandrel and snap it onto the adapter.



Insert the tape screw tip pointed up: your screwdriver is ready!

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®