**Technical Sheet**

CLSA4

# Wood Facade Screw - Stainless A4

The CLSA4 is a double threaded screw suitable for use with timber cladding. The screw consists of type 17 point to prevent timber splitting on insertion and flat head with fiber lock technology which prevents moisture getting into the timber. The double thread ensures sufficient insertion, even in high density wood without the risk of spin-off. It also helps pull the cladding tight to the frame. The CLSA4 screw is made from A4 stainless steel and therefore suitable for use in outdoor environments and extreme weather conditions.







## Features

### Material

- A4 Stainless steel

### Features

- 6 lobe drive
- Flat head with fiber lock technology
- Double threaded
- Extreme ductility
- Type 17 point

## Applications


### Common Applications

- Cladding to timber
- Timber facades to timber

# Technical Sheet

CLSA4
**Wood Facade Screw - Stainless A4**

# Technical Data



## Product Dimensions

| Reference | Fasteners Dimensions | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | Item Code | Other | | Product Dimensions[mm] | | | | |
| | | Box Quantity | Weight[kg] | d[mm] | l[mm] | dh[mm] | lg1[mm] | lg2[mm] |
| CLSA44.8X48 | 75944 | 250.0 | 0.003 | 4.8 | 48 | 8 | 26 | 18 |
| CLSA44.8X65 | 75945 | 250.0 | 0.005 | 4.8 | 65 | 8 | 26 | 22 |

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®