Technical Sheet

TSB

Wood Fiber to Steel Screw - Drill Point

The TSB screw is ideally used indoors for fixing mouldings, OSB, chipboard and plywood to steel. It has a ribbed countersunk flat head which countersinks into the board to ensure a neat finish. The drill point allows the screw to fix boards to steel up to 2mm thick. The TSB screw has a PH2 recess and driver bits are included in every box.



Features

Material

Steel - yellow zinc coating

Features

- PH drive
- Ribbed countersunk head
- Drill point
- Twin thread
- Yellow zinc plated



Applications

Common Applications

- Timber to steel
- Wood fiber board to steel

TSB
Wood Fiber to Steel Screw - Drill Point

Technical Data





Product Dimensions

Reference	Fasteners Dimensions						
	Item Code	Other		Product Dimensions[mm]			
		Box Quantity	Weight[kg]	d[mm]	l[mm]	dh[mm]	Driver Bit[mm]
TSB3.9X28	74276	500.0	0.002	3.9	28	7	PH2

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®