

Technical Sheet


SIMPSON

Strong-Tie

WSC

WSC WOOD FLOORING Screw, Coarse Thread

WSC is a screw with a sharp point and coarse thread, suitable for wood to wood applications such as flooring.



YZP

INDOOR

Features

Material

- Yellow zinc dichromate

Benefits

- Wood to wood applications
- Coarse thread
- WSC32E has Type 17 point and nibs under the head
- WSC38E has a sharp point without nibs under the head
- Bit (BIT2SE) included

Applications

Header member

- Solid wood, composite wood, glued laminated timber,
- Wood frame.

Applications

- Subfloor installation



Technical Sheet


SIMPSON

Strong-Tie

WSC

WSC WOOD FLOORING Screw, Coarse Thread

Technical Data




Product Dimensions UK

Reference	Fasteners Dimensions							
	Product Dimensions[mm]			QD information			Other	
	Head diameter[mm]	Thread Diameter[mm]	Total Length[mm]	Qty per Strip	Recommended RPM[U/Min.]	Compatible Quik Drive Attachment	Qty per Box	Weight[kg]
WSC32E	8.5	4.3	32	30.0	2500 - 4000	QDPR051E / QD76KE	2500.0	0.003
WSC38E	8.5	4.3	38	30.0	2500 - 4000	QDPR051E / QD76KE	2000.0	0.003

WSC

WSC WOOD FLOORING Screw, Coarse Thread

Options

*Countersunk Head with Nibs**Single Thread**Tapered tip*

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

WSC

**WSC WOOD FLOORING Screw,
Coarse Thread**www.strongtie.co.uk**SIMPSON****Strong-Tie®**

2026-10-22